

Vaisala Radiosonde RS41-SGP – accuracy and reliability.



Features

- Superior PTU measurement performance with a pressure sensor
- Automated ground check
- Robust and easy-to-use with informative LEDs
- GPS for continuous wind data availability as well as additional height and pressure calculation
- Stable narrow-band transmission complies with ETSI standard EN 302 054
- Unwinder for consistent sensor boom positioning

RS41 PTU Sensors

Vaisala Radiosonde RS41 temperature sensor utilizes linear resistive platinum technology and is very stable. The small size of the sensor results in low solar radiation error and guarantees fast response. It also incorporates effective protection against evaporating cooling, a phenomenon occasionally encountered when a radiosonde emerges from a cloud top.

The humidity sensor integrates humidity and temperature sensing elements. Pre-flight automatic reconditioning of the humidity sensor effectively removes chemical contaminants and ensures excellent humidity measurement accuracy. The integrated temperature sensor is used to compensate the effects of solar radiation in real time. The sensor heating function enables an active and effective de-icing method at freezing conditions during the flight. The humidity sensor also responds quickly to detect fine structures of the atmosphere.

The pressure sensor is the same high-quality, shock-resistant capacitive silicon sensor as the one in the Vaisala Radiosonde RS92 with revised electronics and calibration.

All RS41 sensors are calibrated against references that are traceable to international standards (SI units), and measurement uncertainties are estimated according to recommendations of the Joint Committee for Guides in Metrology, 100:2008.

RS41 Ground Checks

The in-built temperature sensor check includes a comparison of readings from the temperature element of the humidity sensor and the actual temperature sensor, although no correction to radiosonde measurement is applied.

With the new humidity sensor design, the radiosonde is able to generate physical zero humidity reference more consistently than is possible with

desiccants. The sensor can measure the deviation of humidity measurement at physical zero (0 %RH) and fine-tune the humidity measurement accordingly.

For the pressure measurement ground check, sounding software MW41 displays the RS41 pressure sensor reading difference against an optional barometer module installed inside the ground check device, and adjusts the measurement accordingly. Alternatively an external precision barometer can be used as the reference value and the readings entered manually.

Sensor-based Height and Pressure and GPS-based Wind Data

For meteorological messages, height and pressure measurements utilize the integrated silicon capacitive pressure sensor. Wind is calculated independently based on GPS satellite carrier frequency changes. GPS-based height and pressure measurements are also available for research purposes.

Data Transmission

Vaisala Radiosonde RS41 has a proven data transmission range from radiosonde to receiver of up to 350 km. Data availability during a sounding is guaranteed with digital error-correction code transmission, and telemetry errors are always detected. Due to narrower band transmission, more channels are available in the meteorological frequency band.

Add-on Sensor Connector

RS41 has an interface for additional sensors, primarily to connect it to ozone interface OIF411. Other sensors with Xdata protocol can also be connected. The data is transferred either directly or via a OIF411 interface to the radiosonde and onward to Vaisala DigiCORA® Sounding System MW41.

Technical Data

Measurements

Measurement cycle	1 s
Temperature Sensor	Type: Platinum Resistor
Measurement range	+60 ... -95 °C
Resolution	0.01 °C
Response time (63.2%, 6 m/s flow, 1000 hPa) ¹⁾	0.5 s
Stability (1 year / 3 years)	< 0.05 °C / < 0.1 °C
Accuracy (Repeatability and combined uncertainty with k=2)	
Repeatability in calibration	0.1 °C
Combined uncertainty after ground preparation	0.2 °C
Combined uncertainty in sounding < 16 km	0.3 °C
Combined uncertainty in sounding > 16 km	0.4 °C
Reproducibility in sounding	
> 100 hPa ²⁾	0.15 °C
< 100 hPa ²⁾	0.30 °C
Humidity Sensor	Type: Thin-Film Capacitor
Measurement range	0 ... 100 %RH
Resolution	0.1 %RH
Response time	
6 m/s, 1000 hPa, +20 °C	< 0.3 s
6 m/s, 1000 hPa, -40 °C	< 10 s
Accuracy (Repeatability and combined uncertainty with k=2)	
Repeatability in calibration	2 %RH
Combined uncertainty after ground preparation	3 %RH
Combined uncertainty in sounding	4 %RH
Reproducibility in sounding ²⁾	2 %RH
Pressure	Type: Silicon Capacitor
Measurement range	from surface pressure to 3 hPa
Resolution	0.01 hPa
Accuracy (Repeatability and combined uncertainty with k=2)	
Repeatability in calibration	
> 100 hPa	0.4 hPa
100 - 3 hPa	0.3 hPa
Combined uncertainty in sounding	
> 100 hPa	1.0 hPa
100 - 3 hPa	0.6 hPa
Reproducibility in sounding ²⁾	
> 100 hPa	0.5 hPa
100 - 3 hPa	0.3 hPa
Wind Speed	
Velocity measurement uncertainty ³⁾	0.15 m/s
Resolution	0.1 m/s
Maximum reported wind speed ⁴⁾	160 m/s
Wind Direction	
Directional measurement uncertainty ³⁾	2 deg
Resolution	0.1 deg
Wind direction range	0 to 360 deg

1) After applying time-lag correction, the effect to measurement uncertainty is negligible.

2) Standard deviation of differences in twin soundings, ascent rate above 3 m/s for temperature and humidity

3) Standard deviation of differences in twin soundings. Wind speed above 3 m/s for directional measurement uncertainty.

4) In practice unlimited

Telemetry

Transmitter type	Synthesized
Frequency band	400.15 – 406 MHz
Tuning range	400.16 – 405.99 MHz
Maximum transmitting range	up to 350 km
Frequency stability, 90 % probability	± 2 kHz
Deviation, peak-to-peak	4.8 kHz
Emission bandwidth	According to EN 302 054
Output power (high-power mode)	min. 60 mW
Sideband radiation	According to EN 302 054
Modulation	GFSK
Data downlink	4800 bit/s
Frequency setting	Wireless with ground check device

GPS Receiver (SA Off, PDOP<4)

Number of channels	≥ 48
Frequency	1575.42 MHz, L1 C/A code
Cold start acquisition time	35 s (nominal)
Reacquisition time	1 s (nominal)
Correction	Differential
Reporting resolution of lat, lon position values	1e-8°

Operational Data

Power-up	Wireless with ground check device or with switch
Factory calibration	Stored on Flash memory
Battery	2 pcs AA-size Lithium cells
Operating time	> 240 min
Weight EPS/plastic covers	84 g / 113 g
Dimensions ¹⁾	Body (L x W x H): 155 x 63 x 46 mm Sensor boom bent (L x W x H): 282 x 63 x 104 mm

1) For EPS cover, without wire antenna

Add-on Sensor Support

Protocol support	Xdata to connect several sensors in the same chain, data transferred either directly or via OIF411 to RS41
Transfer rate	max. 200 bytes/s

Unwinder

Material of the string	Non-UV treated polypropylene
Tenacity	< 115 N
Length of the string	55 m
Unwinding speed	0.35 m/s
Weight	25 g

The performance data is expressed with 2-sigma confidence level (k=2), unless otherwise explicitly specified.

For humidity, the performance data is valid T > -60 °C.



Published by Vaisala | B211444EN-G © Vaisala 2018

VAISALA

www.vaisala.com

All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. Any reproduction, transfer, distribution or storage of information contained in this document is strictly prohibited. All specifications — technical included — are subject to change without notice.