

# Intelligent Frequency Converter

F to I / F to V, Models B220-950 / B220-951

## DESCRIPTION

The Blancett Frequency-to-Current (F to I) and Frequency-to-Voltage (F to V) intelligent converters are state-of-the-art active sensors designed to provide enhanced features and greater flexibility for the Blancett turbine.

These microprocessor-based devices are engineered to provide an analog output directly from a Blancett turbine flow meter. The converters measure and calculate the flow rate of a turbine flow meter and produce an analog output proportional to the flow rate. The F to I and F to V converters are offered with either a 4...20 mA or a 0...5V DC output signal, enabling easy electronic integration.

When a converter is ordered with a flow meter, the two components ship from the factory calibrated as a system. If the converter is a replacement, the turbine's K-Factor has changed, or the converter is being used with a different manufacturer's flow meter, then re-programming is possible with an optional Windows®-based software utility. Please consult the factory for details.


## FEATURES

- Converts turbine pulse output into linearized analog output
- Choice of 4...20 mA or 0...5V DC output
- Accuracy of frequency measurement is  $\pm 0.1\%$
- Enables integration with data acquisition devices



## DIMENSIONS

Dimensions are in inches (mm).



Model B220-950 & B220-951

## SPECIFICATIONS


		F to I Model B220-950	F to V Model B220-951
<b>Power</b>		10...30 VDC supply range Loop-powered, 6V insertion loss max	10...26V DC supply range
<b>Inputs</b>	Source	Magnetic Pickup	Magnetic Pickup
	Frequency	0...3500 Hz	0...3500 Hz
	Trigger Sensitivity	30 mV p-p	30 mV p-p
	Frequency Measurement Accuracy	$\pm 0.1\%$	$\pm 0.1\%$
<b>Analog Output</b>	Type	4...20 mA current loop	0...5V DC
	Resolution	1 : 4000	1 : 4000
	Temperature Drift	50 ppm/°C (max)	50 ppm/°C (max)
<b>Environmental</b>	Ambient Temperature	-22...158 °F (-30...70 °C)	-22...158 °F (-30...70 °C)
	Humidity	0...90%, non-condensing	0...90%, non-condensing
	Altitude	2000 m	2000 m
	Use	Indoor/outdoor	Indoor/outdoor

MODELS


Model	Intelligent Converter	Output
B220-950	F to I	4...20 mA
B220-951	F to V	0...5V DC

WIRING DIAGRAMS

F to I Converter, B220-950




F to V Converter, B220-951



Connecting Cables

Model	Length	Description
B220952-6	6 ft	5-pin cable assembly
B220952-15	15 ft	5-pin cable assembly

Male Connector



Control. Manage. Optimize.

Blancett a registered trademark of Badger Meter, Inc. Other trademarks appearing in this document are the property of their respective entities. Due to continuous research, product improvements and enhancements, Badger Meter reserves the right to change product or system specifications without notice, except to the extent an outstanding contractual obligation exists. © 2023 Badger Meter, Inc. All rights reserved.